

# U.S. Battery is proud to introduce the world's only true DEEP CYCLE Group 24, 27 & 31 battery line.

U.S. Battery's Engineering team has specifically designed and engineered these new and innovative products to outperform and outlast the typical "Dual Purpose" or "SLI" types that are commonly found in this market.

U.S. Battery produces our entire line of True Deep Cycle Batteries at our factories in the USA.

U.S. Battery's Innovative "US24DCXC2, US27DCXC2 & US31DCXC2" Deep Cycle Batteries are designed and manufactured using the same plate making technology as our flagship and world famous US2200XC2, along with U.S. Battery's other premium Deep Cycle Batteries. That's the true difference between U.S. Battery and other battery manufacturers. U.S. Battery custom builds every plate that goes into our new and improved **US24DCXC2, US27DCXC2 & US31DCXC2** batteries to hold the maximum amount of energy absorbing paste possible (now with U.S. Battery's proven "XC2" technology). This new process provides Longer Battery Life and Improved Maximum Capacity. All of U.S. Battery's batteries are designed to endure the grueling day-to-day charge and deep discharge cycle that causes most other competing brands to fail prematurely. That won't happen to U.S. Battery's products, as our proven manufacturing processes and techniques will give you years of Reliable and Dependable service. Longer lasting and precision-engineered products are only a few reasons why the U.S. Battery brand is a name the world has trusted for over 88 years. We were here for you then and will be here for you now and for decades to come.

**X**TREME CAPACITY™ with Diamond Plate Technology®



## **X**TREME CAPACITY 2 ADVANTAGES:

- X** Fastest cycle up to full rated capacity.
- X** Highest total energy delivered over the life of the battery.
- X** Ultimate compatibility with the wide range of chargers used in the field.
- X** High charge efficiency designed to meet the new California Energy Commission regulations for combined charger/battery charge efficiency.



[WWW.USBATTERY.COM](http://WWW.USBATTERY.COM)

# US 24 DCXC2 SPECIFICATIONS



5 Hour Rate	68 Ah	Length	11-1/8"
20 Hour Rate	85 Ah	Width	6-3/4"
Min. of Discharge	145 @ 25A.@80°F	Height	9-3/8"
Min. of Discharge	38 @ 75A.@80°F		

# US 27 DCXC2 SPECIFICATIONS

5 Hour Rate	89 Ah	Length	13-3/4"
20 Hour Rate	105 Ah	Width	6-3/4"
Min. of Discharge	205 @ 25A.@80°F	Height	9-3/8"
Min. of Discharge	54 @ 75A.@80°F		



# US 31 DCXC2 SPECIFICATIONS



5 Hour Rate	99 Ah	Length	13"
20 Hour Rate	130 Ah	Width	6-3/4"
Min. of Discharge	225 @ 25A.@80°F	Height	9-3/8"
Min. of Discharge	59 @ 75A.@80°F		



WWW.USBATTERY.COM